Fiber Optic Sensor E3X-DAS



Overview

The E3X-DA-S enables stable long-distance detection even with flexible or extremely thin fibers. Variations in the incident level when inserting the fiber are reduced to half through uniform light distribution. Output pulses may occur when the power is interrupted, so turn OFF the ower to the load or load line before turning OFF the power to the Sensor. Large, easy-to-read displays that are clear even from a distance. These models allow you to use an E3X-DRT21-S VER. safety standards, refer to your OMRON website. Input Specifications ON: Shorted to 0 V (sourcing current: 1 mA max. 5 V to Vcc. short-distance mode. When the MODE Key is pressed once, the power tuning function shifts the power level so that the present incident level is set to the ideal level (2000 on Power Tuning Functio two digital displays.

Article Content

E3X-DA_-S Instruction Manual

When you use the Amplifier Units with Connectors, to prevent electric shock or short-circuits, attach the protector seals provided with E3X-CN-series Connectors to the sides of power supply connectors

E3X-DA-S Datasheet

E3X-DA-S The next-generation platform for a wide range of sensing • The industry''s first Power Tuning function in a digital amplifier. Large, easy-to-read displays that are clear even from a distance. Seven

OMRON E3X-DA-S SERIES MANUAL Pdf Download

© 2026 PROMETHEAS OPTICAL - All rights reserved

View and Download Omron E3X-DA-S Series manual online. Advanced Fiber Amplifier Units. E3X-DA-S Series amplifier pdf manual download. Also for: E3x

Digital Fiber Sensors

The long-term reliable detection at the highest level in the industry is achieved with the innovative APC circuit whose performance is proved by E3X-DA-N series and the newly developed high-power LEDs

E3X-DA-S Datasheet

*1: The optical fiber is 2 m long on each side, so the sensing distance is 4,000 mm. *2: The optical fiber for the E32-T17L is 10 m long on each side, so the value is 20,000 mm

Digital Fiber Sensors E3X-DA-S/MDA

Equipped with an Industry''s First Power Tuning (Optimum Light Setting) Function The E3X-DA-S/MDA features a Power Tuning function that optimizes power at the press of a button.

E3X-DA_-S Instruction Manual

E3X-MC11-S cannot be used. Optical communication are not possible with the E3X-DA-N. Optical communication are possible with the E3X-DA-S or the E3X-MDA. Always keep the protective cover

High functionality digital fiber amplifier

E3X-DA-S High functionality digital fiber amplifier • High functionality digital fiber amplifier with advanced timing, LED power control and signal processing functionality providing highest detection accuracy

E3X-DA-S / MDA Digital Fiber Amplifier

This model allows you to use an E3X-ECT EtherCAT Sensor Communications Unit or E3X-CRT CompoNet Sensor Communications Unit. *2.

E3X-DA-S.fm

E3X-DA-S Tough Fiber Sensor with the World''s Most Stable Detection • With four times the light intensity, the E3X-DA-S provides higher reliability in environments with dust and dirt. Two times the

Digital Fiber Amplifier Unit E3X-DA-S Datasheet

† GIGA RAY for stable detection with the highest leve l of power in this class even for low-reflective objects and large objects. † The E3X-DA0-S supports an EtherCAT Sensor Communications Unit or

© 2026 PROMETHEAS OPTICAL - All rights reserved

Distributed Fiber Optic Sensing | OptaSense

Discover monitoring solutions utilizing distributed fiber optic sensing technology and real-time applications for high-value assets.

E3X-DA-S_MDA_DS_E_11_2

Advanced Fiber Sensors • Features a Power Tuning function that optimizes light reception at the press of a button. APC circuits to suppress LED aging degradation used with 4-element LEDs. 2-channel

E3X-DA-S/MDA

Required performance and functions have been reviewed from basic points to improve high-performance but hard-to-use digital models. Digital fiber sensors, used in the sense as if using volume type

E3X-DA-N Digital Fiber Amplifier/Manual

Discontinued On Mar. 2019 E3X-DA-N Digital Fiber Amplifier The Ultimate Fiber Amplifier for Maximum Ease of Use and High Performance Item list

Digital Fiber Amplifier E3X-DA

Digital Fiber Amplifier Provides High Performance and Ease of Use First amplifier to offer three user-selectable displays: digital level, percentage and analog display Flashing LED and digital display of

E3X-DA-S Digital Fiber Amplifier Unit/Specifications | OMRON

The following temperature ranges apply for operation when an E3X-ECT or E3X-CRT Sensor Communications Unit is used with the E3X-DA0-S: Groups of 1 or 2 Amplifier Units: 0 to

E10E-EN-03+E3X-DA-S+Datasheet

This method is ideal when using a Reflective Fiber Unit to detect workpieces so that detection is not influenced to any great degree by dust and other environmental factors.

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

© 2026 PROMETHEAS OPTICAL - All rights reserved

Contact Us

Continue your research online:

Website: https://prometheas.fr
Technical inquiry: https://prometheas.fr/project-desk.html
North American project region: Ashburn, Loudoun County, Virginia, United States

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 PROMETHEAS OPTICAL - All rights reserved